



## FAB Sheet – Circa Light Guide

FEATURES	ADVANTAGES	BENEFITS
Choice of wattages 23-47W and cover options	Wide range of options to suit application	Improved lighting designs reducing costs
3000K colour temperature	Warm white lighting	Visual comfort and welcoming ambience for pedestrians
Projected LED lifetime L80 after 100,000 hours	Reduces maintenance	Maintenance cost and time savings
International Dark-Sky Association approved	Dark-skies compliant when using a CCT of 3000K or below when mounted horizontal to the carriageway/footway.	Can be used in dark-sky applications in order to protect the night sky from light pollution
High quality pressure die-cast aluminium housing and components	Strong body Corrosion resistant	Suitable for arduous conditions Longer lasting luminaire
Toughened flat glass (0% ULOR) available	Zero upward light	No light pollution
Area and road optics	Directional lighting	Controlled lighting
Light Guide technology – large light emitting, homogenously illuminated surface area	Low glare	Visual comfort for the user of lit environment
CLO (constant light output) available		Energy savings
	Lumen output remains at 100% for 100,000 hrs	Reduced maintenance
		Cost savings
PowerSet feature (integral lumen and power output selection device)	Easy onsite adjustment - no re-programming required	Reduced stock holding Less disruption
		Time and cost savings
Optional dimming and controls	Variable controls and simple upgrades	Increased levels of energy saving
Integral 3-hour emergency option	Continued lighting after mains power failure	Safety for users
IK10 (Bowl) / IK08 (Top) / IP66 ratings	High impact resistance and ingress	Longer life
	protection	Less repair works and costs
	No dust traps	Easier maintenance
Supplied pre-cabled with Arctic Grade PVC flex	No cabling required by contractor	Quicker and easier installation
Post top mounting (76mm or 60mm) Side entry mounting (60mm, 42mm, 34mm)	Variable mounting options	Less stock holding as a universal lantern
UMSUG coded	Separate meter not needed - charging can be included in authorities' overall inventory and single bill	Reduced administration
Manufactured in Britain	Parts required are readily available	Quicker resourcing and assistance
Minimum 10 year warranty	Risk to the contractor and client is reduced	Peace of mind from the backing of an established manufacturer