

ASPECT GEN2

32 LED



IP66
Ingress Protection



IK08
Impact Resistance



8.1kg Weight



Electrical Class I



0.1233m² Wind Area



-20 to 35°C Ambient
(50°C with derated
lumen output)



LED Light Source



TM66 Score
2.7 (Excellent)

SPECIFICATION

- ✓ LED colour temperature PC-Amber*, 2200K, 2700K, 3000K, 4000K (or 5700K Zebra only)
- ✓ Colour rendering index >70 (*>48)
- ✓ Projected L90 after 100,000 hours
- ✓ Power factor >0.95 at full load
- ✓ 1000 hour salt spray compliant, polyester powder coat finish in light grey, dark grey, black or a bespoke colour
- ✓ Marine grade high pressure die cast LM6 aluminium components
- ✓ Stainless steel fixing screws with stainless steel inserts in pivot
- ✓ Toughened ultra efficient safety glass cover (polycarbonate cover optional)
- ✓ Quick release canopy for ease of upgrade
- ✓ Lumi-LinQ wireless exterior lighting control system (optional)
- ✓ Controls - NEMA 7, Zhaga Book 18 (SR) socket (top and/or bottom) and Photocell
- ✓ CLO available
- ✓ PowerSet NFC for external programming of power output, CLO and dimming regimes (manual version available)
- ✓ Part Night Dimming (PND) with manual override option
- ✓ Dim level 10-100%
- ✓ DALI compatible for use with CMS
- ✓ Optional surge protection 10kV/10kA
- ✓ Patented MountSet: Universal system providing post top 60mm or 76mm / side entry 34mm, 42mm, 60mm or 76mm mounting
- ✓ Post top inclination of 0°, +5° and +10°
- ✓ Side entry inclination of -10°, -5°, 0°, +5° and +10°
- ✓ Tool-less access (vandal-proof fixings optional)
- ✓ UMSUG codes available for full product range



DarkSky International approved
Aspect Gen2 32 LED. Compliant when
using a colour temperature of 3000K
or below and at zero degree tilt.

Certified by DarkSky.org



The **PowerSet** module allows on site power adjustment providing maximum flexibility both in-situ and for stock holding. Each module accommodates the selection of any one of the range of UMSUG coded system powers for Aspect Gen2 32 LED.



RANGE OVERVIEW

Type	System Power	Road Optics	Area Optics	CCT	Lumen Output	CRI
A32	37-75W	✓	✓	PC-Amber*, 2200K, 2700K, 3000K, 4000K (or 5700K Zebra only)	11,825lm	>70 (*>48)

ELECTRICAL CHARACTERISTICS

System Power	37-75W
LED CCT	PC-Amber*, 2200K, 2700K, 3000K, 4000K (or 5700K Zebra only)
LED CRI	>70 (*>48)
Lumen Output	11,825lm
Lumen Maintenance	Projected L90 after 100,000 hours
Driver Current	775mA
Driver Output	Constant current output with AM dimming
Power Factor (Full Load/Half Load)	0.95/0.90
Operational Voltage	220-240VAC rms
Operating Frequency	50/60Hz
Inrush Current (Apk/50%-µS)	42A/238µS
Running Current (Max)	329mA
Surge Protection (COM/DIF)	10kV/6kV
Additional Surge Protection (on request)	10kV/10kA
Lighting Controls Options	NEMA 7, Zhaga Book 18 (SR) socket (top and/or bottom), Photocell, Lumi-LinQ, PND and CMS compatible
Controls Protocols	DALI-2 (parts 251 & 253), D4i (optional)

MECHANICAL CHARACTERISTICS

Housing Material	Marine grade high pressure die cast LM6 aluminium components
Cover Material	Toughened ultra efficient safety glass cover (polycarbonate cover optional)
Lens Material	PMMA and polycarbonate options
Housing Finish	Chromate free pre-treatment, polyester powder coat light grey (RAL9006), dark grey (RAL7022), black (RAL9005) or bespoke colours on request
Ingress Protection Rating	IP66
Weight	8.1kg
Wind Area	0.1233m ²
Impact Resistance Rating	IK08 (IK10 with polycarbonate cover)
Mounting Methods	Post top 60mm or 76mm/side entry 34mm, 42mm, 60mm or 76mm
Mounting Inclination	-10°, -5°, 0°, +5° and +10
Photometric Centre	398.5mm (to centre of PCB)

SHIELD OPTIONS

Front	83KIT73648
Rear	83KIT73649
Side	83KIT73650

HIGHWAY SAFETY TETHER KIT OPTIONS

76mm Post Ø	83KIT73829
60mm Post Ø	83KIT73830
42mm Post Ø	83KIT73831
34mm Post Ø	83KIT73832



FOR MORE INFORMATION

+44 (0) 1527 521 162

www.trtlighting.co.uk